

Codice Dianflex: 353-4180

DOSAMAK PRO

Dosatore proporzionale di polifosfato
Scale inhibitor feeder

Cod. prodotto: MKDPT01R
Attacchi: 1"



CARATTERISTICHE

Dosaggio	3 ppm (3mg/L)
Pres. max esercizio	5 bar
Temp. °C	1-45°

Descrizione

I dosatori di polifosfati serie “DOSAMAK PRO” sono stati progettati per essere installati sulle tubature che portano l’acqua nella caldaia per ridurre la presenza di calcare rendendosi molto utili in impianti con acqua dura. Questo filtro/dosatore trova una facile applicazione su caldaie e scaldabagni, prevenendo la possibilità di incrostazioni di calcare, il dosatore è disponibile anche con valvola bypass, per consentire una facile sostituzione della cartuccia una volta esaurita. Grazie alla testa regolabile è possibile installare il dosatore anche negli spazi più ridotti.

Viene fornito completo di:

- Cartuccia con polifosfato, che va cambiata periodicamente.
- Chiave per smontaggio ghiera.
- Guarnizioni.

Materiale costruzione:

- Testata: ottone
- Ghiera: ottone
- Attacchi: ottone
- Guarnizioni: nbr
- Bicchieri: san trasparente atossico

Description

The “DOSAMAK PRO” scale inhibitor feeders series has been designed to be installed on the pipes that bring water into the boiler and prevent scale, making them very useful in presence of hard water. This feeder finds an easy application on boilers and water heaters, preventing the possibility of scale encrustations. feeder finds is available also with bypass valve, to allow easy replacement of the cartridge once exhausted. Thanks to the adjustable head feeder finds can also be installed in the smallest spaces.

It's provided complete of:

- Cartridge with polyphosphate, which must be changed periodically.
- Key for disassembling the ring nut.
- Seals.

Construction materials:

- Head: brass
- Ring nut: brass
- Connections: brass
- Gaskets: nbr
- Bowl: san

Codice Code	Descrizione Description	AxBxC (mm)	Portata Flow rate	Imballo master carton		
				Pz. Pcs	Kg.	AxBxC (cm)
MKDPT01R	Dos. prop. polifosfati att. 1" a 90° (con riduzione 3/4") con bypass. Scale inhibitor feeder 90° - 1" connections (with 3/4" adapters) with bypass – con ghiera	240x100x180	2400-3600 l/h	16	28	56x45x37

